Distribué par : Compteur-energie.com
commercial@compteur-energie.com
+33 (0)3 60 80 00 10

mod.

IWM-PL3

V3.3

Electronic pulse module for multi jet water meters with inductive interface

NFC

ANDROID

Google play

PULSE



Compatible water meters

mod. CPR-M3-I



mod. GMDM-I
mod. GMB-RP-I
mod. GMB-I



ENG

Description

The IWM-PL3 is suitable for remote reading applications in commercial and industrial sectors, acting as an electronic pulse-emitter. It allows the acquisition of the consumption of the counter by third-party systems with a universal interface and integrating advanced counting functions and fraud detections. The use of an inductive target on the meter dial excludes the possibility of magnetic fraud and makes the application insensitive to the pipes vibrations.
The IWM-PL3 is compatible with all the pre-equipped multiple jet meters (wet, semi-dry & dry dial) and allows:

- Consumption analysis (with incremental and decremental counting), reverse flow compensation can be activated for having always perfect alignment between the totalizer and the meter.
- Checking frauds (cable cut and tampering, detection of external magnetic field application, reverse flow). The presence of reverse flow can be monitored with a dedicated impulse contact.
- Dedicated dosing function available for industrial applications.
- IP68 protection* allows the use of the module also for meters installed in difficult environments.
- NFC interface allows configuration and commissioning of the device with the use of a simple smartphone app (available ratio values: 1, 5, 10, 25, 50, 100, 250, 500, 1000), and being able to configure the duration of the output pulse according to the sensitivity of the acquisition system.

Technical features	
Output signal	Supply: maximum 30VDC (100mA) Type: polarized open-collector NPN
Cable length	1,5 meters (4 conductors)
Compatible water meters	CPR-M3-I, GMDM-I, GMB-RP-I, GMB-I
Pulse output minimum value (K)	maximum 1 liter
Energy supply	Non-replaceable lithium battery, 10 years lifetime*
Maximum reading error	0,5%
Protection class	IP68**
Weight	122 g
Size (l x p x h, cable excluded)	88 x 69 x 28 mm
Working Temperature	from +1° to +55°C
Module programming requirements	Android device (smartphone, tablet, etc.) with an NFC interface and the BMetering NFC Config android app APP freely downloadable from GOOGLE PLAY

* The battery life strongly depends on the working time window, set during the configuration process, and on the environmental conditions

** IP68: maximum 24 hours of continuous submersion at 1 m depth



+ WHITE: Pulses
+ YELLOW: Fraud wire
+ GREEN: Third wire
- BROWN: Ground

Cable information	
White	Simple counting wire, NO contact Closes every index revolution, independently from the flow direction.
Yellow	Fraud wire, NC contact, Opens at the following alarm conditions: module removal, inductive target tampering, cable cut, magnetic tampering
Green	Third wire, NO contact, it can be assigned to one of the following features: absolute counting (closes every index revolution during forward flow, with backward flow revolution compensation), backward counting (closes every revolution during back flowing), dosing (closes every XX liter, with XX freely settable)
Brown	Ground (common wire)